

SYNTHETIC COMPRESSOR OIL

Product Code	#6105	#6106	#6107
ISO GRADE	32	68	100
APPROX. SAE NO.	10	20	30
Typical Physical Properties/Test Methods			
API Gravity/ASTM D-287	11.2	14.5	15.8
Wt. Gallon	8.26	8.08	8.00
Specific Gravity/ASTM D-1278	0.9916	0.969	0.960
Flash Point, °F./ASTM D-92	490	500	510
Fire Point, °F./ASTM D-92	550	550	550
Pour Point, °F./ASTM D-97	-60	-40	-20
Viscosity, SUS @ 100°F.	159	336	514
Viscosity, SUS @ 210°F.	47.2	53.7	58.5
Viscosity Index/ASTM D-2270	157	95	67
Viscosity, cst @ 210°F./ASTM D-445	6.4	8.4	9.8
Viscosity, cst @ 100°F./ASTM D-445	33.8	72.4	111.1
Viscosity, cst @ 0°F.	954	8311	28,663
Viscosity, cst @ -20°F.	2860	44,840	---
Auto Ignition/ASTM D-2155	765	765	765
Evaporation, 22 hours at 210°F., %/ASTM D-972	0.20	0.10	0.20

Note: The 10W SYNTHETIC COMPRESSOR OIL is not recommended for reciprocating (piston) type compressors.

Handling Information: For safe handling of the product, read the Material Safety Data Sheet (MSDS).

[Home](#)[Product Information](#)[Prev](#)[Next](#)