



NU FLOOR FINISH CONCENTRATE

USER BENEFITS:

- **PROTECTS MULTIPLE INDOOR SURFACES**
- **DRIES QUICKLY TO HIGH GLOSS**
- **EASY CARE, NON-YELLOWING**
- **RUGGED WEAR ONE STEP SEAL AND FINISH**

NU FLOOR FINISH CONCENTRATE is a modified acrylic product for indoor surfaces. It seals and finishes in one step and cures in 30 minutes to a high gloss. It is slip-resistant, detergent and waterspot resistant, and its hard, resilient finish impedes black heel marks.

Protects Multiple Surfaces

NU FLOOR FINISH CONCENTRATE utilizes the latest advancements in polymer technology to help give floors lustrous, long-lasting protection. A synthetic liquid polymer emulsion, NU FLOOR FINISH CONCENTRATE is perfect for use on all types of natural and synthetic indoor flooring, including:

Asphalt Tile
Rubber Tile
Vinyl Tile
Brick Pavers
Sealed Wood

Terrazzo
Marble
Quarry Tile
Painted Concrete
Smooth Concrete

Dries Quickly To High Gloss

NU FLOOR FINISH CONCENTRATE dries to a high gloss luster in about 30 minutes. For



greater shine, finish responds beautifully when buffed with standard equipment or polished with the new high-speed or ultra, high-speed burnishing machines.

Easy Care, Non-Yellowing

NU FLOOR FINISH CONCENTRATE exhibits outstanding resistance to most detergents commonly recommended for cleaning floors. Non-yellowing, it rarely needs stripping. High traffic areas coated with ACRYLENE may be spot patched without showing overlap.

Rugged Wear Seal and Finish

NU FLOOR FINISH CONCENTRATE dries to a hard, resilient finish which impedes black heel marks and, for added safety, is slip resistant. Normal cleaning will not harm the finish — it's both mild detergent and water spot resistant.

Three Convenient Sizes

This floor finish is available in 3 convenient sizes - 1 gallon, 2 gallon, and 5 gallon pail. It is also concentrated, so a 1 gallon pail yields 2 gallons of product, etc.

DIRECTIONS FOR USE:

Strip and clean floor using TRC's QUADRA-KLEAN Industrial Cleaner. Remove all soil and old finish. To take advantage of NU FLOOR FINISH CONCENTRATE's coverage rate, use of a nylon loop mop is recommended. If a nylon loop mop is not readily available, a sweeper/mop with an acrylic/polyester head is recommended.

Like any floor finish, NU FLOOR FINISH CONCENTRATE should be applied with single strokes of the mop in one pass, making sure that the entire floor is coated. If floor is badly worn, additional coats may be necessary. Allow 20 to 40 minutes drying time between coats, depending upon humidity and ventilation. The second coat should be applied lightly, never rubbed in. While in most cases, NU FLOOR FINISH CONCENTRATE will dry to the touch in 1 - 2 hours, a full 8 hours should be allowed before traffic is permitted.

Worn areas may be patch-coated as needed. Clean by mopping with mild cleaner such as TRC's BIG RED. Recoat as needed with NU FLOOR FINISH CONCENTRATE.

COVERAGE RATES:

Typical coverage is 2,000 square feet per gallon per coat. This product is in concentrated form and should be mixed with water. 1 part concentrate with 1 part water.

SPECIFICATIONS

NU FLOOR FINISH CONCENTRATE

Product Code: #103291

NU FLOOR FINISH CONCENTRATE is a 16% solids metal cross-linked, modified acrylic floor finish. It seals and finishes in one step and cures naturally to a high gloss. Being a metal cross-linked, modified acrylic floor finish, it is slip resistant, detergent resistant and water spot resistant. It gives excellent results when buffed and can be patched without showing overlap. It dries to a hard, resilient finish which resists black heel marks. NU FLOOR FINISH CONCENTRATE is not to be used outside where it can be exposed to rain or other water sources.

Physical Form	Water Based Emulsion
Color	Milky White Liquid; Dries Clear
Flash Point	None To Boiling
% Solids	16
Density	8.5 lbs./gallon
Specific Gravity	1.02 ± 0.01
pH (concentrate)	8.2 - 8.6
Shelf Life	1 Year
Storage Temperature Range	40° F. - 90° F
D.O.T. Shipping Label	None

Handling Information: For safe handling of the product, read the Safety Data Sheet (SDS).

Tele: (817) 332-1161
Toll Free: 1-800-827-0711
FAX: (817) 332-1366
Toll Free Fax: 1-877-540-7464
Web: www.texasrefinery.com

Protective Coatings Division
TEXAS REFINERY CORP
TEXAS • ONTARIO • SASKATCHEWAN

PRINTED IN U.S.A. 2019
P204510