



WB RAINSEAL

USER BENEFITS:

- **REPELS WATER**
- **PROTECTS MASONRY**
- **LONG-LASTING**
- **ECONOMICAL**
- **SAFE AND EASY TO APPLY**

WB RAINSEAL is a water-repellent coating which protects above ground masonry from the damaging effects of moisture. Its long-lasting formulation is economical and easy to use.

Repels Water

WB RAINSEAL contains a minimum 7% silicone to coat each tiny pore of masonry. Water strikes the surface and is unable to penetrate, forcing the water to roll harmlessly to the ground. While WB RAINSEAL provides a tough film, it allows normal and necessary air circulation through the masonry surface.

Protects Masonry

Water first attacks unprotected mortar joints, causing unsightly efflorescence. Over time, water can dissolve or erode these unprotected areas. WB RAINSEAL protects masonry surfaces and helps keep walls clean and free of efflorescence and the damaging effects of water. In addition, WB RAINSEAL protected walls stay cleaner because dirt has no place to anchor itself and rolls off with the rain.



We sprayed this brick wall with water after treating part of it with WB RAINSEAL. See the difference?

Dries Clear

WB RAINSEAL has a milky-white opaque appearance, but dries clear. It will not stain walls or other surfaces. It will not change the color or texture of the protected masonry.

Long-Lasting

When WB RAINSEAL is properly applied, a long-lasting bond is made with the masonry surface. One good application should keep masonry walls cleaner and water repellent for five years or longer. WB RAINSEAL is excellent in all climates.

Safe and Easy To Apply

WB RAINSEAL is ready for use just as it comes from the container. It is easily applied by brush, roller or airless sprayer. Do not apply WB RAINSEAL to painted surfaces.

Economical

WB RAINSEAL saves money in three important ways. (1) The water-repellent qualities of WB RAINSEAL protect the building investment. (2) Upkeep costs are dramatically reduced. (3) The easy application of WB RAINSEAL saves valuable time.

COVERAGE

POROUS MASONRY

(Haydite Block)

1 gal. to 75 sq. ft. of area

MEDIUM TEXTURE MASONRY

(Cement Wall)

1 gal. to 100 or 125 sq. ft. of area

FINE TEXTURE MASONRY

(Well-Burned Brick)

1 gal. to 200 sq. ft. of area

SPECIFICATIONS

WB RAINSEAL

Product Code #103157

USE: Repels water from masonry surfaces including Limestone, Sandstone, Granite, Artificial and Real Brick, Castone, Stucco and Terracotta. Helps control efflorescence to promote a clean appearance while providing water repellent surface.

PHYSICAL REQUIREMENTS:

Composition	Advanced Water/Silane/Siloxane blend
Solvent Content	0.0%
Flash Point, °F., PMCC	>185°F
Total Solids, Wt. %	7%
VOC Compliant	Yes
Appearance	Milky White
Drying Time	4 Hours
Maximum Water Repellency	3 Days
Normal Shelf Life (Unopened)	1 Year
Temperature Range for Storage	0-100°F.

CAUTION: Keep out of reach of children. For safe handling of this product, read the Safety Data Sheet (SDS).

Tele: (817) 332-1161
Toll Free: 1-800-827-0711
FAX: (817) 332-1366
Toll Free Fax: 1-877-540-7464
Web: www.texasrefinery.com

Protective Coatings Division
TEXAS REFINERY CORP
TEXAS • ONTARIO • SASKATCHEWAN

PRINTED IN U.S.A. 2019
P20103157