



ACRYLENE FLOOR FINISH

USER BENEFITS:

- **PROTECTS MULTIPLE INDOOR SURFACES**
- **DRIES QUICKLY TO HIGH GLOSS**
- **EASY CARE, NON-YELLOWING**
- **RUGGED WEAR ONE STEP SEAL AND FINISH**

ACRYLENE FLOOR FINISH is a modified acrylic product for indoor surfaces. It seals and finishes in one step and cures in 30 minutes to a high gloss. It is slip-resistant, detergent and waterspot resistant, and its hard, resilient finish impedes black heel marks.

ACRYLENE FLOOR FINISH Protects Multiple Surfaces

ACRYLENE FLOOR FINISH utilizes the latest advancements in polymer technology to help give floors lustrous, long-lasting protection. A synthetic liquid polymer emulsion, ACRYLENE FLOOR FINISH is perfect for use on all types of natural and synthetic indoor flooring, including:

Asphalt Tile
Rubber Tile
Asbestos Tile
Vinyl Tile
Vinyl Asbestos Tile
Brick Pavers

Sealed Wood
Terrazzo
Marble
Quarry Tile
Painted Concrete
Smooth Concrete

ACRYLENE FLOOR FINISH Dries Quickly To High Gloss

ACRYLENE FLOOR FINISH dries to a high gloss luster in about 30 minutes. For greater



shine, finish responds beautifully when buffed with standard equipment or polished with the new high-speed or ultra, high-speed burnishing machines.

ACRYLENE FLOOR FINISH Easy Care, Non-Yellowing

ACRYLENE FLOOR FINISH exhibits outstanding resistance to most detergents commonly recommended for cleaning floors. Non-yellowing, it rarely needs stripping. High traffic areas coated with ACRYLENE may be spot patched without showing overlap.

ACRYLENE FLOOR FINISH Rugged Wear Seal and Finish

ACRYLENE FLOOR FINISH dries to a hard, resilient finish which impedes black heel marks and, for added safety, is slip resistant. Normal cleaning will not harm the finish — it's both mild detergent and water spot resistant.

ACRYLENE FLOOR FINISH is an advanced sealer and finish all in one.

FOR INDOOR USE ONLY

DIRECTIONS FOR USE:

Strip and clean floor using TRC's QUADRA-KLEAN Industrial Cleaner. Remove all soil and old finish. Using a medium strip mop or a lambs-wool applicator, apply ACRYLENE FLOOR FINISH in thin, even coats. If floor is badly worn, additional coats may be necessary. Allow 20 to 40 minutes drying time between coats, depending upon humidity and ventilation. The second coat should be applied lightly, never rubbed in. Worn areas may be patch-coated as needed. Clean by mopping with mild cleaner such as TRC's MULTI-KLEAN. Recoat as needed with ACRYLENE FLOOR FINISH.

COVERAGE RATES:

Smooth Texture...300 sq. ft. per gal.
Medium Texture...200 sq. ft. per gal.
Rough Texture.....100 sq. ft. per gal.

SPECIFICATIONS

ACRYLENE FLOOR FINISH

Product Code: #4510

ACRYLENE FLOOR FINISH is a 16% solids metal cross-linked, modified acrylic floor finish. It seals and finishes in one step and cures naturally to a high gloss. Being a metal cross-linked, modified acrylic floor finish, it is slip resistant, detergent resistant and water spot resistant. It gives excellent results when buffed and can be patched without showing overlap. It dries to a hard, resilient finish which resists black heel marks. ACRYLENE FLOOR FINISH is not to be used outside where it can be exposed to rain or other water sources.

Physical Form	Water Based Emulsion
Color	Milky White Liquid; Dries Clear
Flash Point	None To Boiling
% Solids	16
Density	8.5 lbs./gallon
Specific Gravity	1.02 ± 0.01
pH (concentrate)	8.2 - 8.6
Shelf Life	1 Year
Storage Temperature Range	40° F. - 90° F
D.O.T. Shipping Label	None

Handling Information: For safe handling of the product, read the Safety Data Sheet (SDS).

Tele: (817) 332-1161
Toll Free: 1-800-827-0711
FAX: (817) 332-1366
Toll Free Fax: 1-877-540-7464
Web: www.texasrefinery.com

Protective Coatings Division
TEXAS REFINERY CORP.
Fort Worth, Texas
Toronto, Ontario • Moose Jaw, Saskatchewan

PRINTED IN U.S.A. 2/2014
P204510