



BACKER ROD

Flexible Foam Filler

It's the perfect filling material for deep cracks and joints in concrete and asphalt before a weatherproofing application of NU-FLOOR FLEX-JOINT or POURABLE CRACK FILLER.

- Saves on Sealer and Money when used in deep cracks
- Lightweight and flexible
- Fast and easy to use

MEASURING AND APPLICATION

The size of BACKER ROD should be slightly larger (about $\frac{1}{2}$ ") than the width of the crack it's being used in.

Cleaning and/or routing may be necessary before installation. To install, simply force the BACKER ROD into the crack or joint, cutting to desired length with knife or scissors. Proper position of BACKER ROD in crack is about $\frac{1}{2}$ " to $\frac{3}{4}$ " below surface.

Then, use NU-FLOOR FLEX-JOINT (for concrete) or POURABLE CRACK FILLER (for asphalt) over the BACKER ROD to complete the repair.

CONVENIENT SIZES

Flexible Foam Filler BACKER ROD is available in lengths of 75 feet, in three convenient diameters (widths):

3/8" x 75'	Product Code # 2625
1/2" x 75'	Product Code # 2626
1" x 75'	Product Code # 2627

**Call Texas Refinery Corp. at Toll Free:
1-800-827-0711 if additional information
is needed.**

Handling Information: For safe handling of the product,
read the Safety Data Sheet (SDS).

Tele: (817) 332-1161
Toll Free: 1-800-827-0711
FAX: (817) 332-1366
Toll Free Fax: 1-877-540-7464
Web: www.texasrefinery.com



Protective Coatings Division

TEXAS REFINERY CORP.

Fort Worth, Texas
Toronto, Ontario • Moose Jaw, Saskatchewan

**PRINTED IN U.S.A. 2/2014
P202625**