# CHUCK HOLE PATCHING MATERIAL

## USER BENEFITS:

- **FOR ASPHALT PAVEMENT REPAIR**
- **READY TO USE**
- **EASY TO APPLY**

CHUCK HOLE PATCHING MATERIAL is an asphalt coated aggregate used to repair small holes and broken areas in blacktop and paved areas. CHUCK HOLE PATCHING MATERIAL is ready to use as it comes from the container, requires no mixing or measuring.

*Chuck holes can be dangerous and lead to costly damage.*

## CHUCK HOLE PATCHING MATERIAL For Asphalt Pavement Repair

Chuck holes (potholes) are dangerous and can lead to costly damage. Left untreated, they allow water to enter the apshlat and compromise the integrity of the base. In addition, they can damage vehicle traffic and present the risk of injury to foot traffic. Chuck holes have no ability to self-correct. They must be repaired.

## CHUCK HOLE PATCHING MATERIAL Ready To Use

CHUCK HOLE PATCHING MATERIAL requires no heating. It is ready to use just as it comes from the container. No mixing or measuring needed. For best results during cold weather, keep container in a warm, dry place for a few days prior to using. Temperature of product should be raised to at least 80°F and used immediately..

*TRC CHUCK-HOLE PATCHING MATERIAL quickly and effectively prepares parking areas for traffic.*

## CHUCK HOLE PATCHING MATERIAL Easy To Apply

CHUCK HOLE PATCHING MATERIAL is easy to use by following the step-by-step instructions on the following page. The need for expensive contract labor or infrared heat-applied patches is eliminated.

### APPLICATION INSTRUCTIONS:

1. Locate and mark all chuck holes and broken areas. Brush, sweep or blow all dust and loose aggregate from each chuck hole. Clean each one down to a firm base.

2. Coat the chuck hole sparingly with QUICK-DRY ASPHALT PENETRATING PAVING SEAL. Do not allow it to puddle in the bottom of the hole. Allow to cure a minimum of two hours.

3. Fill the hole heaping full of CHUCK HOLE PATCHING MATERIAL. Tamp it firmly into place with a crown effect, about ½" higher in the center than at the edges. Allow it to set for about 12 hours or overnight.

4. Once the repair has cured to a firm surface, QUICK-DRY ASPHALT PENETRATING PAVING SEAL can be used to seal over it. Allow several weeks before final sealing.

# SPECIFICATIONS

CHUCK HOLE PATCHING MATERIAL

Product Code #3085

| | |
|---|---|
| Use: | Designed especially for repairing small holes and broken areas in black-top or asphalt-paved areas. This product is cold applied and requires no mixing. |
| Color: | Black |
| Weatherability: | Good in Arid, Tropical and cold climates. |

Physical Requirements - Typical:

| | |
|---|---|
| Asphalt, % (Soxhlet Extraction) | 7% |
| Ash Content, % by Wt. | 93% |
| Wt./Gallon - packed | 14.9 lbs. |
| unpacked | 10.3 lbs. |

| | |
|---|---|
| Coverage: | One 6-gallon container will fill a volume 3 inches deep and 2 feet in diameter. |

Specifications Met:

Texas Highway Standard Specification
Hot Mix Cold Laid Asphaltic Concrete Pavement
Item 350
FF Grade

Handling Information: For safe handling of the product, read the Safety Data Sheet (SDS).

*Protective Coatings Division*
**TEXAS REFINERY CORP.**
Fort Worth, Texas
Moose Jaw, Sask. • Toronto, Ontario

**Tele: (817) 332-1161**
**Toll Free: 1-800-827-0711**
**FAX: (817) 332-1366**
**Toll Free Fax: 1-877-540-7464**
**Web: www.texasrefinery.com**

PRINTED IN U.S.A. 5/2014
P203085