

GLAS-WEB

(For Use in Conjunction with MIGHTYPLATE PLASTIC CEMENT to Repair Blisters, Bulges, Cracks or Breaks in Roof Membranes)



SPECIFICATIONS

Product Code # 3030

Description And Uses:

GLAS-WEB is constructed of pure glass fiber with a thread positioning coat of special organic coating designed for MIGHTYPLATE Asphalt Products.

USE: Provide added strength in roofing repairs and construction.

COMPATIBILITY: The GLAS-WEB saturant is a combination of synthetic resins and natural asphalt in the proper balance to give complete compatibility with all accepted waterproofing and coating compounds.

FLEXIBILITY: No cracking of the Mightyplate coated GLAS-WEB shall take place on bending over a 1/32" Mandrel through an arc of 180 degrees in one direction and through 360 degrees over the same Mandrel in the opposite direction.

WEIGHT*:	Per Roll (6" x 150 ft.)	0.93 lbs. (0.4 kg)
	Per Roll (12" x 150 ft.)	1.9 lbs. (0.9 kg)
	Per Roll (36" x 150 ft.)	5.6 lbs. (2.6 kg)
	Per Area	1.8 oz. / sq. yd. (61.0 gm/sq.m.)

TENSILE STRENGTH*:	WARP (Typical)	100 lbs. / linear inch	(17.86 kg / cm)
	FILL (Typical)	95 lbs. / linear inch	(16.97 kg / cm)

* Weight and Tensile Strength figures are normal values. Average Tensile Strength is usually much greater.

NOTE: Read carefully and follow application instructions in the booklet -
HOW TO APPLY MIGHTYPLATE.

Handling Information: For safe handling of products, read the Safety Data Sheet (SDS).