

#1 NEATSFOOT OIL

- PRESERVES LEATHER
- PENETRATES & PROTECTS
- NUMEROUS USES
- MARKET ACCEPTANCE
- TREMENDOUS POTENTIAL
- ECONOMICAL

#1 NEATSFOOT OIL is an amber colored oil that is composed of natural lubricants and is compatible with various types of leather.

#1 NEATSFOOT OIL Preserves Leather

Through the years many methods of preserving leather have been tried; however, nothing equals or does a better job than #1 NEATSFOOT OIL. #1 NEATSFOOT OIL does not rot stitching.

#1 NEATSFOOT OIL Penetrates & Protects

Many products darken leather. #1 NEATSFOOT OIL gives only a slight color change to the leather. There is excellent penetration to provide the protection needed for the investment in leather.



#1 NEATSFOOT OIL penetrates and protects leather and does not rot stitching.

#1 NEATSFOOT OIL Has Numerous Uses

Each day potential Customers can be discovered. Farmers, saddle-makers, rodeo clubs, ranchers, riding clubs, harness shops, trainers, horse associations, stables, and many other outlets use #1 NEATSFOOT OIL.

#1 NEATSFOOT OIL Has Market Acceptance

Some Customers buy #1 NEATSFOOT OIL in drums and repackage in sizes their trade requires. Some Customers purchase 6 gallon pails, retailing them to their trade. Others buy some in all sizes, retailing some and using some themselves.

#1 NEATSFOOT OIL Has Tremendous Potential

There are over 700,000 quarter horses in the lower 48 states today. Considering the thousands of other horses, just imagine the potential for #1 NEATSFOOT OIL. It staggers the imagination.

#1 NEATSFOOT OIL Is Economical

If there has ever been a "sleeping giant," #1 NEATSFOOT OIL has to be it. Texas Refinery Corp. is one of the very few suppliers of

#1 NEATSFOOT OIL. Unlike most of the competition, it does not spoil or turn sour. This very stable product is also economical. A little goes a long way. In addition, the pricing is very reasonable compared even to inferior products. No doubt you will enjoy using Texas Refinery Corp.'s #1 NEATSFOOT OIL.

SPECIFICATIONS

#1 NEATSFOOT OIL
Product Code #6190

TESTS	MINIMUM	MAXIMUM	TYPICAL
Specific Gravity	0.8811	0.8922	0.8866
Viscosity at 210°F., SUS	35	40	39
Viscosity at 100°F., SUS	100	110	105
Viscosity Index	50		74.6
Flash Point, ⁰ F.	320		325
Fire Point, ⁰F.	340		345

 $\label{thm:condition:equation:of the product, read the Safety Data Sheet (SDS). \\$

Toll Free: 1-800-827-0711
Toll Free Fax: 1-800-582-3329
www.texasrefinery.com
E-mail: lube1@texasrefinery.com

TEXAS REFINERY CORP
TEXAS • ONTARIO • SASKATCHEWAN